

JOB NAME _____
SALES REP _____
ARCHITECT _____
DESIGNER _____
BUILDER _____
INSTALLER _____

Rake Board

STANDARD SPECIFICATIONS

APPLICATION Wall Paneling
CONSTRUCTION Solid
THICKNESS 3/4"
WIDTHS 3 1/2" - 5 1/2"
LENGTHS Random 2' to 12'
PANELING PROFILE Square

LEED MR-4 100% Post Consumer

SPECIES Mixed Species
SURFACE Original Surface/Milled
FINISH Unfinished

Rake board can be crafted with silver grey board, brown board, or with other custom accent colors. (silver grey board pictured)

INTERNAL PRODUCT REFERENCE _____



Due to the nature of reclaimed wood, variation in color, texture, and character will occur.

CHARACTER Mild Checking | Nail Holes | Some Knots | Color Variance

APPLICATION Walls

INSTALLATION As a general guideline for wall board, we suggest that it is installed over plywood. Installation methods vary greatly depending on site conditions and application. Please feel free to contact us to verify installation methods.

All material is kiln dried for stability. Widths and lengths listed ship in standard lead times. Wider widths and custom sizes available for extended lead times. Upcharge may apply to single widths, wider widths, and additional customizations.

** Prefinishing is available on select products and will incur an upcharge. Please inquire for more information.*



Surface Architectural Supply
1504 Belleville St
Richmond, VA 23230
(804) 918-2467
www.surface-supply.com