

JOB NAME _____
SALES REP _____
ARCHITECT _____
DESIGNER _____
BUILDER _____
INSTALLER _____

Reclaimed Oak

STANDARD SPECIFICATIONS

APPLICATION	Wall Paneling
CONSTRUCTION	Solid
THICKNESS	3/8", 5/8", or 3/4"
WIDTHS	3 1/2" - 5 1/2"
LENGTHS	Random 2' to 12'
PANELING PROFILE	Square
LEED	MR-4 100% Post Consumer
SPECIES	Reclaimed Mixed Oak
SURFACE	Original Surface
FINISH	Water Clear Finish



INTERNAL PRODUCT REFERENCE _____

Due to the nature of reclaimed wood, variation in color, texture, and character will occur.

CHARACTER Mild Checking | Nail Holes | Some Knots | Mineral Stains | Saw Kerf | Color Variance

APPLICATION Floors | Walls | Tops | Treads | Doors

INSTALLATION As a general guideline for wall board, we suggest that it is installed over plywood. Installation methods vary greatly depending on site conditions and application. Please feel free to contact us to verify installation methods.

All material is kiln dried for stability. Widths and lengths listed ship in standard lead times. Wider widths and custom sizes available for extended lead times. Upcharge may apply to single widths, wider widths, and additional customizations.

** Prefinishing is available on select products and will incur an upcharge. Please inquire for more information.*



Surface Architectural Supply
1504 Belleville St
Richmond, VA 23230
(804) 918-2467
www.surface-supply.com