

JOB NAME \_\_\_\_\_  
SALES REP \_\_\_\_\_  
ARCHITECT \_\_\_\_\_  
DESIGNER \_\_\_\_\_  
BUILDER \_\_\_\_\_  
INSTALLER \_\_\_\_\_

## Toasted Pine

### STANDARD SPECIFICATIONS

**APPLICATION** Wall Paneling  
**CONSTRUCTION** Solid  
**THICKNESS** 3/4"  
**WIDTHS** 3 1/2" - 5 1/2"  
**LENGTHS** Random 2' to 12'  
**PANELING PROFILE** Square

**LEED** MR-4 100% Post Consumer

**SPECIES** Reclaimed Pine  
**SURFACE** Toasted Pine  
**FINISH** Water Clear Finish

**INTERNAL PRODUCT REFERENCE** \_\_\_\_\_



*Due to the nature of reclaimed wood, variation in color, texture, and character will occur.*

**CHARACTER** Mild Checking | Nail Holes | Some Knots | Color Variance | Raised Grain

**APPLICATION** Walls

**INSTALLATION** As a general guideline for wall board, we suggest that it is installed over plywood. Installation methods vary greatly depending on site conditions and application. Please feel free to contact us to verify installation methods.

*All material is kiln dried for stability. Widths and lengths listed ship in standard lead times. Wider widths and custom sizes available for extended lead times. Upcharge may apply to single widths, wider widths, and additional customizations.*

*\* Prefinishing is available on select products and will incur an upcharge. Please inquire for more information.*



**Surface Architectural Supply**  
1504 Belleville St  
Richmond, VA 23230  
(804) 918-2467  
[www.surface-supply.com](http://www.surface-supply.com)