

JOB NAME \_\_\_\_\_  
SALES REP \_\_\_\_\_  
ARCHITECT \_\_\_\_\_  
DESIGNER \_\_\_\_\_  
BUILDER \_\_\_\_\_  
INSTALLER \_\_\_\_\_

---

## Hatteras

---



### **STANDARD SPECIFICATIONS**

<b>APPLICATION</b>	Flooring, Wall Paneling
<b>CONSTRUCTION</b>	Engineered
<b>THICKNESS</b>	5/8" or 3/4"
<b>LENGTHS</b>	Random 2' to 10'
<b>FLOORING WIDTHS</b>	3", 4", 5", 6", 7" and 8"
<b>FLOORING PROFILE</b>	Tongue & Groove
<b>PANELING WIDTHS</b>	3.5", 4.5" and 5.5"
<b>PANELING PROFILE</b>	Square
<b>LEED</b>	MR-4 100% Post Consumer
<b>SPECIES</b>	Reclaimed Oak
<b>SURFACE</b>	Hit and Miss
<b>FINISH</b>	Hatteras, Oil Finish

**INTERNAL PRODUCT REFERENCE** \_\_\_\_\_

*Due to the nature of reclaimed wood, variation in color, texture, and character will occur.*

**CHARACTER** Mild Checking | Nail Holes | Some Knots | Saw Kerf | Color Variation

**APPLICATION** Floors | Walls | Tops | Treads | Doors

**INSTALLATION** Our flooring products should be installed following NWFA installation methods. As a general guideline for wall board, we suggest that it is installed over plywood. Installation methods vary greatly depending on site conditions and application. Please feel free to contact us to verify installation methods.

*All products are fabricated to order with a lead time of 4 - 6 weeks. A shorter lead time may be available if the product is ordered within standard specifications and is in stock. Custom specifications such as wider widths, single widths, customized finishes, etc. are available by client request and may have an upcharge or extended lead time. Speak to your Surface Architectural Supply sales representative for more information and details.*



**Surface Architectural Supply**  
(804) 918-2467  
[www.surface-supply.com](http://www.surface-supply.com)