

JOB NAME _____
SALES REP _____
ARCHITECT _____
DESIGNER _____
BUILDER _____
INSTALLER _____

Oshima

STANDARD SPECIFICATIONS

| | |
|---------------------|---------------------------|
| APPLICATION | Wall Paneling |
| CONSTRUCTION | Solid |
| WIDTHS | 5 1/8" |
| LENGTHS | 8', 10' or 12' |
| THICKNESS | 3/4" |
| PROFILE | Tongue and Groove |
| SPECIES | Southern Yellow Pine |
| SURFACE | Heavy Crackle |
| FINISH | Charred with Clear Finish |



INTERNAL PRODUCT REFERENCE _____


Due to the organic nature of wood, variation in color, texture, and character will occur.

CHARACTER Mild Checking | Some Knots | Color Variation

APPLICATION Walls | Box Beams | Doors

INSTALLATION Our flooring products should be installed following NWFA installation methods. As a general guideline for wall board, we suggest that it is installed over plywood. Installation methods vary greatly depending on site conditions and application. Please feel free to contact us to verify installation methods.

All products are fabricated to order with a lead time of 4 - 6 weeks. A shorter lead time may be available if the product is ordered within standard specifications and is in stock. Custom specifications such as wider widths, single widths, customized finishes, etc. are available by client request and may have an upcharge or extended lead time. Speak to your Surface Architectural Supply sales representative for more information and details.



Surface Architectural Supply
(804) 918-2467
www.surface-supply.com