

JOB NAME _____
SALES REP _____
ARCHITECT _____
DESIGNER _____
BUILDER _____
INSTALLER _____

Oshima

STANDARD SPECIFICATIONS

APPLICATION	Wall Paneling
CONSTRUCTION	Solid
THICKNESS	3/4"
WIDTHS	5 1/8"
LENGTHS	8', 10' or 12'
PANELING PROFILE	Tongue and Groove
LEED	Not eligible for MRc4
SPECIES	New Growth Pine
SURFACE	Charred
FINISH	Prefinished



INTERNAL PRODUCT REFERENCE _____

Due to the nature of the fabrication of this product some variation in color, texture, and character will occur.

CHARACTER Mild Checking | Nail Holes | Some Knots | Color Variance | Raised Grain

APPLICATION Walls

INSTALLATION As a general guideline for wall board, we suggest that it is installed over plywood. Installation methods vary greatly depending on site conditions and application. Please feel free to contact us to verify installation methods.

All material is kiln dried for stability. Widths and lengths listed ship in standard lead times. Wider widths and custom sizes available for extended lead times. Upcharge may apply to single widths, wider widths, and additional customizations.

** Prefinishing is available on select products and will incur an upcharge. Please inquire for more information.*



Surface Architectural Supply
1504 Belleville St
Richmond, VA 23230
(804) 918-2467
www.surface-supply.com